



(11) EP 0 912 082 A1

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**28.04.1999 Bulletin 1999/17**

(51) Int. Cl.<sup>6</sup>: **H05K 13/04**, **B65D 73/02**

(21) Application number: **98119622.3**

(22) Date of filing: 16.10.1998

**(84) Designated Contracting States:**  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
**Designated Extension States:**  
**AL LT LV MK RO SI**

(30) Priority: 27.10.1997 JP 294148/97

(71) Applicant:  
**SUMITOMO BAKELITE COMPANY LIMITED**  
**Tokyo 140 (JP)**

(72) Inventor:  
**Mikami, Shinichi,**  
**c/o Sumitomo Bakelite Co., Ltd.**  
**Tokyo (JP)**

(74) Representative:  
Vossius, Volker, Dr. et al  
Dr. Volker Vossius,  
Patentanwaltskanzlei - Rechtsanwaltskanzlei,  
Holbeinstrasse 5  
81679 München (DE)


## Remarks:

A request for correction of the description and claim 3 has been filed pursuant to Rule 88 EPC. A decision on the request will be taken during the proceedings before the Examining Division (Guidelines for Examination in the EPO, A-V, 3.).

(54) **Carrier tape for electronic components**

(57) The present invention provides a carrier tape for electronic components comprising a flexible tape material having embossed portions (2) for storing electronic components at regular intervals in the lengthwise direction of the tape, characterized in that each of the opposing first and third side walls of the embossed portion which are positioned at both sides of the lengthwise direction of the tape, has a pair of first protrusions A for preventing the electronic component from transverse shaking which protrude inwardly in the embossed portion, and optionally further has, between the protrusions A, a plurality of second protrusions B for preventing the electronic component from longitudinal shaking which differ in shape from the protrusions A. According to one preferred embodiment of the present invention, the carrier tape for electronic components has, at the bottom surface of the embossed portion, two or more central protuberances in the direction perpendicular to the lengthwise direction of the carrier tape. The carrier tape of the present invention prevents rupture of the electronic components caused by vibrations or trembles of the electronic components during transportation and, furthermore, improves inspection ability at optical inspection at the time of insertion of the electronic components and thus further improves productivity.

FIG. 1



## Descripti n

[0001] The present invention relates to an article for packaging and carrying components, particularly, to a carrier tape for electronic components which is used for packaging and carrying electronic components such as IC.

[0002] Hitherto, carrier tapes as shown in FIG. 9 have been known as such tapes. The carrier tape 1 is made of a flexible resin material and comprises two portions of a recess 2 (hereinafter referred to as "embossed portion 2") and a flange portion 3. A plurality of the embossed portions 2 are arranged at equal spaces along the length of the carrier tape 1 (in the lengthwise direction of the tape) and are used for storing one electronic component in one embossed portion. The flange portion 3 is used for allowing a tape-like cover (hereinafter referred to as "cover tape") to adhere thereto so that the electronic components stored do not fall off from the openings of the embossed portions during transportation of the components, and has a number of perforations arranged at equal spaces on both or one side of the tape in the lengthwise direction.

[0003] The carrier tape 1 used for packaging and carrying electronic components is intermittently fed at an interval of the distance between the embossed portions 2 at the time of insertion of electronic components into the embossed portions 2, inspection of the electronic components or adhering of the cover tape as shown in FIGS. 10 and 11. In this intermittent feeding, the electronic components inserted in the embossed portions 2 move in horizontal direction together with the carrier tape 1, and when it stops at the position for inspection of the electronic components, the position varies at every feeding to cause miss-recognition or miss-operation of the inspection device. Furthermore, when the carrier tape 1 is stopped, sometimes the electronic component in the embossed portion is pressed against the wall surface in the moving direction by the inertia action of the electronic component's own weight and stops in the state of the lead part of the electronic component contacting with the wall surface. This state causes severe miss-operation or miss-recognition by the inspection device which utilizes a reflected light of an optical illuminator, because the reflected light from the lead and the reflected light from the wall surface are banded together and indistinguishable.

[0004] Moreover, after insertion and inspection of the electronic components and adhesion of the cover tape, the carrier tape 1 is wound on reel 5 and then is transported. During the transportation, the reel 5 storing the electronic components may receive various unexpected external forces such as a shock caused by unexpected dropping, and a vibration and shock caused by movement. Owing to the shock and vibration, the electronic component comes to contact with the wall surface and the bottom surface of the embossed portion 2 of the carrier tape 1, which sometimes leads to contamination or

distortion of the lead part. In addition, in the case of the embossed portion 2 having the shape as shown in FIG. 9 which illustrates the conventional carrier tape, unexpected shock causes distortion of the embossed portion 2, which leads to distortion or rupture of the lead part of the electronic component.

[0005] Furthermore, generally, the carrier tape 1 is made from a flexible resin material (sheet-like material) and thereafter the embossed portions 2 are formed. In the molding of the embossed portions 2, the residual stress generated at the time of molding is concentrated at the corners of the embossed portions, resulting in a phenomenon of distortion of the flange portion 3 in the form of protuberance. This distortion in the form of protuberance exerts a bad influence of increase in scatter of peel strength when the cover tape is peeled off for taking out the electronic components from the carrier tape 1. As a result, the peeling speed of the cover tape cannot be enhanced and breakage of the cover tape is brought about or the carrier tape 1 is shaken above the surface mounting apparatus. This is not preferred for the improvement of mounting efficiency of electronic components.

[0006] In view of the above problems, the present invention provides a carrier tape for electronic components according to which vibration and shake of the electronic components in the embossed portions are diminished and scatter in peel strength of the cover tape is decreased.

[0007] The present invention relates to a carrier tape for electronic components having embossed portions for storing electronic components which are arranged at regular intervals in the lengthwise direction of the tape, wherein the opposing first and third side walls positioned on both sides of the embossed portion in the lengthwise direction of the tape, respectively have a pair of first protrusions A for preventing the electronic component from transverse shaking and, if necessary, a plurality of second protrusions B different in shape from the protrusions A are provided between the pair of the protrusions A for preventing the electronic component from longitudinal shaking. According to one preferred embodiment of the present invention, the distance between the pair of the protrusions A ("A-A" in FIG. 4) is larger by 0.05-0.5 mm than the length of the electronic component in the lengthwise direction of the carrier tape, said distance between the pair of the protrusions A being measured at the position thereof apart by the distance of 1/2 ("e" in FIG. 4) of the length of the electronic component in the direction perpendicular to the lengthwise direction of the tape from the center of the embossed portion, and the wall surface forming the protrusions A which prevent transverse shaking of the electronic component, forms an angle of 3-45° with the lengthwise direction of the tape, and besides, the distance between the tops of the protrusions A in the direction perpendicular to the lengthwise direction of the tape ("At-At" in FIG. 4) is larger by 0.05-2 mm than the dis-

tance between the outermost sides of the lead part of the electronic component ("Y" in FIG. 4). According to another preferred embodiment of the present invention, the difference between the shortest distance between two protrusions B in the direction perpendicular to the lengthwise direction of the carrier tape and the length of the electronic component in the direction perpendicular to the lengthwise direction of the tape is 0.1-1 mm ("B-E" in FIG. 8) and is smaller than the difference ("(At-At)-Y") between the distance between the tops of the protrusions A in the direction perpendicular to the lengthwise direction of the tape ("At-At" in FIG. 4) and the distance between the outermost sides of the lead part of the electronic component ("Y" in FIG. 4). According to further another preferred embodiment of the present invention, the bottom surface forming the embossed portion has two or more central protuberances in the direction perpendicular to the lengthwise direction of the carrier tape.

FIG. 1 is a plan view of the carrier tape of Example 1.

FIG. 2 is a lengthwise sectional view of the carrier tape of Example 1.

FIG. 3 is a sectional view of the carrier tape of Example 1 in the direction perpendicular to the lengthwise direction of the tape.

FIG. 4 is a partially enlarged view of the carrier tape of FIG. 1.

FIG. 5 is a plan view of the carrier tape of Example 2.

FIG. 6 is a lengthwise sectional view of the carrier tape of Example 2.

FIG. 7 is a sectional view of the carrier tape of Example 2 in the direction perpendicular to the lengthwise direction of the tape.

FIG. 8 is a partially enlarged view of the carrier tape of FIG. 5.

FIG. 9 is an oblique view of a conventional carrier tape for electronic components.

FIG. 10 is a diagram which shows the steps of insertion of electronic components, optical inspection of the electronic components and adhesion of a cover tape in using a carrier tape.

FIG. 11 is a diagram of intermittent feeding of the carrier tape for electronic components.

FIG. 12 schematically shows residual stress at molding and waving phenomenon of the flange portion in the conventional carrier tape.

FIG. 13 schematically shows residual stress at molding and waving phenomenon of the flange portion in the carrier tape of Example 1.

FIG. 14 schematically shows residual stress at molding and waving phenomenon of the flange portion in the carrier tape of Example 2.

[0008] The reference numerals and signs in FIG. 1 to FIG. 14 have the following meanings.

[0009] 1: Carrier tape; 2: Recess (embossed portion); 3: Flange portion; 4: Perforations; 5: Reel; 6: Protrusion A; 7: Protrusion B; 8: Central protuberance; 9: Body of electronic component; 10: Lead part; 11: Residual stress trajectories; 12: Waviness in flange portion; 13: Cover tape; 14: Electronic component inserting section; 15: Electronic component-optically inspecting section; 16: Cover tape adhering section; s: Starting of insertion of electronic component; i: The first feeding; ii: The second feeding; iii: The third feeding; iv: The fourth feeding; v: The fifth feeding; IP: Insertion position of electronic component; x: The lengthwise direction of carrier tape for electronic components; e: Distance of 1/2 of length of electronic component in the direction perpendicular to the x direction; A-A: Distance between a pair of protrusions A (in the x direction) at the position thereof apart by the distance e from the center of the embossed portion; At-At: Distance between tops of protrusions A in the direction perpendicular to the x direction; Y: Distance between outermost sides of electronic component lead part; B-E: Difference between the shortest distance between two protrusions B in the direction perpendicular to the x direction and the length of electronic component in the direction perpendicular to the x direction; (At-At)-Y: Difference between At-At and Y.

[0010] According to the present invention, the body of the electronic component is prevented from transverse shaking by the protrusions A provided at a distance corresponding to the size of the electronic component to be stored in the embossed portion. Thus, lengthwise (x direction) movement of the electronic component is prevented during transportation to inhibit contact between the lead part and the side walls, thereby to prevent contamination and bending of the lead part and miss-recognition or miss-operation of inspection device at the time of inspection.

[0011] Furthermore, longitudinal shaking of the electronic component is prevented by a plurality of the protrusions B provided between the protrusions A. Thus, movement of the electronic component in the direction perpendicular to the lengthwise direction (x direction) is prevented during transportation to inhibit contact between the lead part and the side walls, thereby to prevent contamination and bending of the lead part.

[0012] Moreover, by providing the protrusions A and the protrusions B, the residual stress generated at the formation of the embossed portions in a flexible resin sheet can be dispersed and diminished.

[0013] Furthermore, the electronic component can be prevented from trembling during transportation by supporting the bottom portion of the electronic component by two or more central protuberances provided at the bottom of the embossed portion in the direction perpendicular to the lengthwise direction of the tape, and thus contamination and bending of the lead part can be prevented.

[0014] When an unexpected external force is applied to the electronic component from above, the central pro-

tuberances receive the external force at the bottom portion of the electronic component to reduce the force applied to the lead part, whereby the damage and distortion of the lead part can be minimized.

[0015] As explained above, the present invention has realized a carrier tape for electronic components which has the following advantages. That is, contamination, distortion and bending of the lead part of electronic component can be prevented; miss-recognition and miss-operation of inspection device for the electronic component are inhibited; scatter of peel strength at the time of peeling of the cover tape is diminished; and the tape is excellent in holding and protecting of electronic components, optical inspection ability for the inserted electronic components, and mounting operability in surface mounting.

[0016] Examples of the present invention will be explained in detail with reference to the accompanying drawings.

#### Example 1

[0017] FIGS. 1-3 show a carrier tape 1, in which embossed portions 2 are formed so that a plurality of IC packages such as SOP (Small Outline Package), SSOP (Shrink Small Outline Package), TSOP (Thin Small Outline Package), TSSOP (Thin Shrink Small Outline Package) and PLCC (Plastic Leaded Chip Carrier) can be stored therein. In this carrier tape 1, two protrusions A:6 are formed at the first and third side walls of the embossed portion 2 which are in the lengthwise direction of the tape, among the side walls of the embossed portion 2, and two central protuberances 8 are formed at the bottom of the embossed portion 2 in the direction perpendicular to the lengthwise direction of the tape.

[0018] As shown in FIG. 4, the distance A-A between a pair of the protrusions A:6 is preferably larger by 0.05-0.5 mm than the length of the electronic component in the lengthwise direction of the tape, said distance being measured at the positions of the protrusions apart from the center of the embossed portion by the distance e which is 1/2 of the length of the electronic component in the direction perpendicular to the lengthwise direction of the carrier tape. If the difference in distance is less than 0.05 mm, there is the possibility that the electronic component cannot be inserted in the embossed portion 2 due to variation in the size. If it is more than 0.5 mm, the electronic component is apt to move owing to vibration.

[0019] Furthermore, as shown in FIG. 4, it is preferred that the distance At-At between the tops of the protrusions A:6 in the direction perpendicular to the lengthwise direction of the tape is larger by 0.05-2 mm than the distance Y between the outermost sides of the lead part of the electronic component. If the difference in distance is less than 0.05 mm, there is the possibility that the electronic component cannot be inserted in the embossed portion 2 due to variation in the size. If it is more than 2 mm, the electronic component is apt to

move owing to vibration.

[0020] Furthermore, it is preferred that the wall surface of the protrusion A:6 which prevents transverse shaking of the electronic component, forms an angle of 3-45° with the lengthwise direction of the tape. If the angle is smaller than 3°, the wall surface of the protrusion A:6 nearly contact with the surface of the body of the electronic component, and hence, insertion of the electronic component becomes difficult. If it is greater than 45°, it becomes difficult to prevent transverse shaking of the electronic component, and besides, scatter of residual stress generated by molding of the embossed portion becomes insufficient.

[0021] In the above construction, the protrusions A:6 prevent transverse shaking of the four corners of the electronic component 9 stored in the embossed portion 2, and even when a vibration is applied to the carrier tape 1 during transportation, the lead part 10 is held with keeping a certain space from the second and fourth side walls of the embossed portion 2 as shown in FIGS. 1-3.

[0022] Moreover, conventionally, in the formation of the embossed portion 2, the thickness of the central part of the bottom becomes greater, causing variation in bottom thickness. As a result, the bottom of the electronic component 9 is nearly supported at one point and trembling of the electronic component is often seen. However, when two central protuberances 8 are formed, the bottom of the electronic component 9 is supported at these two portions and trembling caused by vibration of the carrier tape 1 is diminished, whereby collision of the lead part 10 against the bottom of the embossed portion 2 can be avoided. In addition, when an unexpected external force acts on the electronic component 9, the external force does not directly act on the lead part 10, but acts on the body of the electronic component 9.

[0023] Conventionally, residual stress generated by the formation of the embossed portions 2 is concentrated to the corners of the embossed portions 2, resulting in great waviness of the flange portion 3 at intervals of the embossed portions as shown in FIG. 12. However, by providing a pair of protrusions A:6 at each of the first and third side walls of the embossed portion 2 which are positioned at both sides of the lengthwise direction of the carrier tape, the residual stress is also scattered to the portions of the protrusions A:6 and the waviness of the flange portion 3 is reduced as shown in FIG. 13.

#### Example 2

[0024] The carrier tape in this Example is the same as that in Example 1, except that two protrusions B:7 are formed between the protrusions A:6 provided at the first and third side walls of the embossed portion 2 which are positioned in the lengthwise direction of the tape among the side walls of the embossed portion 2 as shown in

FIGS. 5-7. The protrusions B:7 do not protrude beyond the protrusions A:6 in the direction perpendicular to the lengthwise direction of the carrier tape and are formed so as to prevent longitudinal shaking of the end faces of the body of the electronic component 9.

[0025] It is preferred that the shortest distance (B) between two protrusions B:7 in the direction perpendicular to the lengthwise direction of the carrier tape is larger by 0.1-1 mm than the length (E) of the electronic component in the direction perpendicular to the lengthwise direction of the carrier tape. If the difference in distance is less than 0.1 mm, sometimes, the electronic component cannot be inserted in the embossed portion 2 due to variation in the size. If it is more than 1 mm, the electronic component is apt to move by the vibration and further, the electronic component is apt to turn in the embossed portion.

[0026] Moreover, as for the protrusions B:7, it is preferred that the difference of B (the shortest distance) - the length of the electronic component (E) is smaller than the difference [(At-At)-Y] between the distance between the tops of the protrusions A (At-At in FIG. 4) and the distance (Y in FIG. 4) between the outermost sides of the lead part of the electronic component as shown in FIG. 8. If B-E is larger than (At-At)-Y, the lead part readily contacts with the protrusions A to suffer from contamination.

[0027] In the above construction, as shown in FIG. 5, the protrusions A:6 prevent transverse shaking of the four corners of the electronic component 9 stored in the embossed portion 2, and, besides, the protrusions B:7 prevent longitudinal shaking of the body per se of the electronic component 9. Thus, as compared with the case where no protrusions B:7 are provided, the electronic component 9 is inhibited from turning horizontally and the electronic component 9 is stably held, even when vibration is applied to the carrier tape 1 during transportation.

[0028] Moreover, by the formation of the additional protrusions B:7 at the first and third side walls of the embossed portion 2 which are positioned at both sides of the lengthwise direction of the carrier tape, the residual stress generated by the formation of the embossed portions 2 is further scattered by the protrusions B:7 and the waviness of the flange portion 3 is further diminished as shown in FIG. 14.

#### Claims

1. A carrier tape for electronic components comprising a flexible tape material having embossed portions for storing electronic components at regular intervals in the lengthwise direction of the tape, characterized in that the opposing first and third side walls of the embossed portion which are in the lengthwise direction of the tape, respectively have a pair of protrusions A for preventing the electronic component from transverse shaking which protrude

inwardly in the embossed portion.

2. A carrier tape for electronic components comprising a flexible tape material having embossed portions for storing electronic components at regular intervals in the lengthwise direction of the tape, characterized in that the opposing first and third side walls of the embossed portion which are in the lengthwise direction of the tape, respectively have a pair of first protrusions A for preventing the electronic component from transverse shaking which protrude inwardly in the embossed portion, and further have, between the protrusions A, a plurality of second protrusions B for preventing the electronic component from longitudinal shaking which differ in shape from the protrusions A.
3. A carrier tape for electronic components according to claim 1 or 2, wherein the distance between the pair of the protrusions A ("A-A" in FIG. 4) is larger by 0.05-0.5 mm than the length of the electronic component in the lengthwise direction of the carrier tape, said distance between the pair of the protrusions A being measured at the position thereof apart from the center of the embossed portion by the distance of 1/2 ("e" in FIG. 4) of the length of the electronic component in the direction perpendicular to the lengthwise direction of the tape; the wall surface forming the protrusions A which prevent transverse shaking of the electronic component, forms an angle of 3-45° with the lengthwise direction of the tape; and the distance ("At-At" in FIG. 4) between the tops of the protrusions A in the direction perpendicular to the lengthwise direction of the tape is larger by 0.05-2 mm than the distance (Y in FIG. 4) between the outermost sides of the lead part of the electronic component.
4. A carrier tape for electronic components according to claim 2 or 3, wherein the difference ("B-E" in FIG. 8) between the shortest distance between two protrusions B in the direction perpendicular to the lengthwise direction of the carrier tape and the length of the electronic component in the direction perpendicular to the lengthwise direction of the tape is 0.1-1 mm and is smaller than the difference ("(At-At)-Y" in FIG. 8) between the distance ("At-At" in FIG. 4) between the tops of the protrusions A in the direction perpendicular to the lengthwise direction of the tape and the distance ("Y" in FIG. 4) between the outermost sides of the lead part of the electronic component.
5. A carrier tape for electronic components according to claim 1, 2, 3 or 4, wherein the bottom surface forming the embossed portion has two or more central protuberances in the direction perpendicular to the lengthwise direction of the carrier tape.

FIG. 1




FIG. 2




FIG. 3




FIG. 7




FIG. 4




FIG. 8






FIG. 5




FIG. 6




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 98 11 9622

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	PATENT ABSTRACTS OF JAPAN vol. 097, no. 007, 31 July 1997 & JP 09 066964 A (KANEKO DENKI KK), 11 March 1997 * abstract *	1-5	H05K13/04 B65D73/02
A	--- PATENT ABSTRACTS OF JAPAN vol. 095, no. 009, 31 October 1995 & JP 07 149393 A (HITACHI LTD;OTHERS: 01), 13 June 1995 * abstract *	1-5	
A	--- US 5 351 821 A (SKRTIC THOMAS) 4 October 1994 * figures 2,3 *	1-5	
A	--- WO 92 14348 A (MINNESOTA MINING & MFG) 20 August 1992 * figures 1,5,8 *	1-5	
A	--- US 5 524 765 A (GUTENTAG CHARLES) 11 June 1996 * the whole document *	1-5	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.8)
			H05K B65D
Place of search		Date of completion of the search	Examiner
MUNICH		5 February 1999	Torti, C
CATEGORY OF CITED DOCUMENTS			
<p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/92 (P04/C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 9622

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-02-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5351821 A	04-10-1994	DE 69311962 D	14-08-1997
		DE 69311962 T	12-02-1998
		EP 0568034 A	03-11-1993
		EP 0756448 A	29-01-1997
		JP 6056168 A	01-03-1994
		US 5396988 A	14-03-1995
WO 9214348 A	20-08-1992	DE 69205969 D	14-12-1995
		DE 69205969 T	04-07-1996
		EP 0571510 A	01-12-1993
		ES 2079184 T	01-01-1996
		JP 6505220 T	16-06-1994
		SG 50491 A	20-07-1998
		US 5361901 A	08-11-1994
US 5524765 A	11-06-1996	NONE	

EPO FORM P/469

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X ① ✓	PATENT ABSTRACTS OF JAPAN vol. 012, no. 395 (E-671), 20 October 1988 (1988-10-20) -& JP 63 136527 A (NEC CORP), 8 June 1988 (1988-06-08) * abstract * -& DATABASE WPI Section Ch, Week 198829 Derwent Publications Ltd., London, GB; Class L03, AN 1988-200452 XP002146036 * abstract *	1-8	H01L21/68
X ② ✓	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 11, 30 September 1999 (1999-09-30) -& JP 11 151661 A (SPEEDFAM CO LTD), 8 June 1999 (1999-06-08) * abstract * * paragraphs '0004!', '0007!', '0012!', '0019!' *	1-8	
X ③ ✓	PATENT ABSTRACTS OF JAPAN vol. 018, no. 225 (E-1541), 22 April 1994 (1994-04-22) -& JP 06 021220 A (SEIKO EPSON CORP), 28 January 1994 (1994-01-28) * abstract * * paragraphs '0001!', '0004!', '0008!', '0011!', '0012!' * -& DATABASE WPI Section EI, Week 199409 Derwent Publications Ltd., London, GB; Class U11, AN 1994-069733 XP002146037 * abstract *	1-8	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H01L
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 29 September 2000	Examiner Munnix, S
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	



DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
(4) X ✓	PATENT ABSTRACTS OF JAPAN vol. 014, no. 336 (E-0953), 19 July 1990 (1990-07-19) -& JP 02 112258 A (SEIKO EPSON CORP), 24 April 1990 (1990-04-24) * abstract *	1-8	
(5) A ✓	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 02, 30 January 1998 (1998-01-30) -& JP 09 272850 A (NITTO DENKO CORP), 21 October 1997 (1997-10-21) * abstract *	2,4,6-8	
(6) D,A ✓	EP 0 157 508 A (NITTO ELECTRIC IND CO) 9 October 1985 (1985-10-09) * abstract *	5	
(7) D,A ✓	WO 95 32834 A (RICHERZHAGEN BERNOLD) 7 December 1995 (1995-12-07) * abstract *	1-8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 29 September 2000	Examiner Munnix, S
<div>CATEGORY OF CITED DOCUMENTS</div> <div>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</div> <div>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</div>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 6824

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-09-2000

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
JP 63136527	A	08-06-1988	NONE		
JP 11151661	A	08-06-1999	NONE		
JP 06021220	A	28-01-1994	NONE		
JP 02112258	A	24-04-1990	NONE		
JP 09272850	A	21-10-1997	NONE		
EP 0157508	A	09-10-1985	JP	1940230 C	09-06-1995
			JP	6016524 B	02-03-1994
			JP	60196956 A	05-10-1985
			DE	3586329 A	20-08-1992
			DE	3586329 T	10-12-1992
			US	5637395 A	10-06-1997
			US	5714029 A	03-02-1998
WO 9532834	A	07-12-1995	US	6010782 A	04-01-2000
			DE	4418845 C	28-09-1995
			DE	19518263 A	07-12-1995
			EP	0762947 A	19-03-1997
			JP	10500903 T	27-01-1998
			US	5902499 A	11-05-1999